

HEATER PROOFERS - INSULATED

35% ENERGY SAVINGS!

100% PRE-TESTED ELECTRICAL ASSEMBLY

- Heavy Duty, aluminum construction designed for durability.
- Easy to Clean.
- Forced air design provides even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Front casters are provided with brakes.
- Easy dual proof/heat control: Available in Digital (DGT) and Analog Design
- "Proof/humidity" mode: Up to 95% RH at 110°F (43°C)
- "Heat" mode: Maximum Temperatures up to 180°F (82°C)
- Corner bumpers provide protection to unit, associates & fixtures.
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on the inside door frame.
- Door opens 270 degrees. Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- Drip Trough catches condensation. Internal water pan collects condensation or is used in proofer mode.
- All controls are accessible without opening cabinet door. Easy to read real time LED thermometer display.
- Pan Capacity: 35 - 18" x 26" pans

Electrical specifications:

- 120 Volt-60 Hz, NEMA 5-15P
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



INHPL-1836C-DGT

Model Number	Order#	Overall Dimensions			Approx. Ship Wt (lb)
		Width (in)	Length (in)	Height (in)	
INHPL-1836C-DGT	1079013	23	30½	68	185
INHPL-1836C	684609	23	30½	68	185

Caster Information

Swivel Plate Caster with 5" Polyurethane Wheel 738A (128784)
 Swivel Plate Caster with 5" Polyurethane Wheel & Brake 738ABK (204185)
 5" Polyurethane Wheel 7112 (122180)

Freight Class: 175

